

<i>Name of the document</i> Declaration of confirmity Interior panel of spruce, painted or white-waxed	<i>Document nr.</i> CPR1097	<i>Page</i> 1 of 2
<i>Prepared by</i> Michaela Pfeiffer	<i>Number of edition</i> 1	
<i>Approved by</i> Lars Kristen Holst	<i>Replaces edition</i> -	<i>Date of edition</i> 2022-10-28

DECLARATION OF CONFIRMITY – CPR1097

1. Productgroup and identification

Sawn, planed or profiled wooden panels with or without spruce battens. The panel is available with the surface layers coated, hard waxed or white waxed and has a thickness of ≥ 14 mm.

2. Product information

Top-painted, hard-waxed and white-waxed, sawn, planed or profiled wooden panels with or without battens.

For additional or more detailed information about delivered product, in addition to what is stated below, see package specification or any attached commercial document.

3. The intended use of the product

Panel intended for walls and ceilings, interior use.

4. Manufacturer

Company: [Moelven Wood AB](#)
Adress: [Box 8006, 650 08 Karlstad, Sweden](#)
Telephone: [+46 10 122 50 50](#)
E-mail: order.woodab@moelven.se
Webbsite: www.moelven.com

5. System for assessment and continuous of the construction product's performance

System 3 in AVCP.

6. Certification and stated performance

The product is produced according to the harmonized standard EN 14915.

The notified body MEKA (identification number 2040) has carried out fire tests to check fire growth rate, flammability and smoke growth. MEKA has issued a classification report in accordance with EN 13501-1.

The specified standard that is followed has no replacement standard for the UK, but also applies to complying with the UKCA.



<i>Name of the document</i> Declaration of conformity Interior panel of spruce, painted or white-waxed	<i>Document nr.</i> CPR1097	<i>Page</i> 2 of 2
<i>Prepared by</i> Michaela Pfeiffer	<i>Number of edition</i> 1	
<i>Approved by</i> Lars Kristen Holst	<i>Replaces edition</i> -	<i>Date of edition</i> 2022-10-28

7. Declared performance


Essential characteristics	Declared values		
Reaction to fire	Fireclass		
	Euroclass	D-s2,d0 according to EN 13501-1	
	Substrate		
	Mounting	Minimum density [kg/m³]	Fireclass (EN 13501-1)
	With vented, non-ventilated or without air gap	525	A1/A2-s1, d0
Thermal conductivity	25,2 (according to EN 14915)		
Application	I – Interior (according to CEN TS 15912)		
Intened area of use	W - Wall and C - Cieling		
Wood species	PCAB (spruce)		
Durability	4 (according to EN 350-2)		
Density	440 kg/m ³		
Sound absorption	0,10/0,30 (according to EN 14915)		
Water vapor permeability	20 (wet)/50 (dry) (according to EN 14915)		
Release of formaldehyde	E1		
Content of pentachlorophenol	NPD (no performance detected)		
Hazardous substances	NPD (no performance detected)		
Resistant to fixing	NPD (no performance detected)		

8. Additional technical documentation

The property of the product declared in section no.1 and 2 is in accordance with the property stated in section no.7. This declaration of performance is prepared under the responsibility of the manufacturer specified in Section No. 4.

Karlstad 2022-02-28

Lars Kristen Holst, manager product management


.....
(signature)